



## HFC

Contamination can occur wherever open radioactive material is used. An HFC contamination monitor has to be used to check personnel leaving controlled areas. The limit values of surface contamination are defined specifically for each nuclide. Our HFC-monitors are available in various models and versions, all **made in Germany**.

## BENEFITS

- No gas-filled or gas-flushed detector
- 2 in 1 instrument:  $\alpha$ - und  $\beta/\gamma$ -contamination measurement with only one detector, no detector change required
- Detachable hand probe, no additional frisker probe required
- Background measurement and subtraction
- User-friendly interface via touch screen
- Network-compatible

## KEY FIGURES

2-6 detectors  
various version

5 models available

43-94 cm  
system width

## FIVE BASIC MODELS

Depending on specific requirements and available space, you can choose one of the following models from our extensive product line.

### BaseLine

Our HFC BaseLine model meets all expectations for a user-friendly hand-foot-clothing contamination monitor. Like all our HFC models it can be upgraded with a number of options (see below) and adapted to individual requirements.

### SlimLine

The HFC SlimLine with hand detectors integrated in the front panel is ideal for use in small areas. Optional transport wheels and a handle allow the system to be easily relocated. Like the BaseLine model, it is available with single or double hand detectors. You can even choose between vertically or horizontally mounted hand detectors.

### TrendLine

The HFC TrendLine incorporates the latest result of our continuous product development in an elegant housing. The state-of-the-art PC technology with large touch-screen allows intuitive operation and provides virtually unlimited networking and data transfer options, as well as connection of printers, transponders or card readers.



### CrossLine

The HFC CrossLine is designed as a walk-through monitor. Like all our HFC monitors it has output relays available for door controls or other interlocks to ensure everyone is free of contamination before leaving the area.

### EcoLine

The HFC EcoLine is a compact, cost effective solution in case only the hands need to be measured. This model is based on the same technology and electronics as the entire HFC line.



**BaseLine**



**SlimLine**



**TrendLine**



**CrossLine**



**EcoLine**

## PRODUCT SPECS

- Innovative detector technology based on thin-layer plastic scintillation detectors
- No gas-filled or gas-flushed detectors, low operating and maintenance costs
- Simultaneous, selective  $\alpha$ - and  $\beta/\gamma$ -contamination measurement, no need to change detectors
- Measuring system automatically detects and indicates whether  $\alpha$ -radiation is present
- PC-based measuring electronics
- User-friendly interface, large-area colour display
- Nuclide selection menu, user-configurable
- Personal-related measurement via selection menu, card, barcode or transponder
- Hand probe detachable for clothing measurement, no additional frisker probe required
- Integrated calibration software (auto-calibration)
- Ergonomic housing design with stainless steel front
- Network-compatible
- Software available for data administration and parameter setting
- Calibration according to DIN ISO 7503 or DIN 25482
- **Optional:** detection limit calculation according to DIN ISO 11929

## VERSIONS

Our HFC monitors are available in various versions. You can select the number and position of the hand detectors as well as the size of the foot detectors.

The following table lists the different options per model. The combination of the letters shows the version.

### Example:

BaseLine **HF** is the BaseLine model in the version with 2 hand detectors and 2 normal foot detectors.

| Model     | 2 hand horizontal | 4 hand horizontal | 4 hand vertically | 2 feet normal | 2 feet bigfoot |
|-----------|-------------------|-------------------|-------------------|---------------|----------------|
| BaseLine  | H                 | D                 | V                 | F             | B              |
| SlimLine  | H                 | D                 | V                 | F             | B              |
| TrendLine | H                 | D                 |                   | F             | B              |
| CrossLine |                   |                   | V                 | F             | B              |
| EcoLine   | H                 |                   |                   |               |                |

## OPTIONS

| Model     | Transport wheels | Transponder | Admin software | Special card reader / barcode |
|-----------|------------------|-------------|----------------|-------------------------------|
| BaseLine  | ✓                | ✓           | ✓              | ✓                             |
| SlimLine  | ✓                | ✓           | ✓              | ✓                             |
| TrendLine | ✓                | ✓           | ✓              | ✓                             |
| CrossLine |                  | ✓           | ✓              | ✓                             |
| EcoLine   |                  | ✓           | ✓              | ✓                             |

| Radionuclide efficiency for hand detector<br>(average values from measurements with 100 cm <sup>2</sup> sources) |     |                                  |     |
|--|-----|----------------------------------|-----|
| Am-241 α   | 20% | K-40                             | 30% |
| Au-198   | 23% | P-32                             | 25% |
| C-14   | 13% | Pu-238 α                         | 12% |
| Cl-36  | 42% | Re-188                           | 20% |
| Co-57  | 8%  | S-35                             | 5%  |
| Co-60  | 30% | Sr-90 / Y-90<br>(based on Sr-90) | 46% |
| I-123  | 7%  | Tc-99 m                          | 4%  |
| I-125  | 12% | Tl-201                           | 6%  |
| I-131  | 20% | Tl-204                           | 23% |

| Radionuclide efficiency for foot detector<br>(average values from measurements with 100 cm <sup>2</sup> sources) |     |                                  |     |
|--|-----|----------------------------------|-----|
| Am-241 α   | 13% | K-40                             | 18% |
| Au-198   | 14% | P-32                             | 15% |
| C-14   | 6%  | Pu-238 α                         | 7%  |
| Cl-36  | 27% | Re-188                           | 12% |
| Co-57  | 5%  | S-35                             | 3%  |
| Co-60  | 17% | Sr-90 / Y-90<br>(based on Sr-90) | 31% |
| I-123  | 5%  | Tc-99 m                          | 2%  |
| I-125  | 7%  | Tl-201                           | 4%  |
| I-131  | 12% | Tl-204                           | 14% |

## Options



### Transport wheels

Mounted castors and hand grip



### Transponder

Transponder system for automatic identification of personnel, containing identification system and software expansion



### ADMIN Software

For remote data administration and parameter setting

## Made in Germany



NUVIATech Instruments uses exclusive know-how and state-of-the art technologies in its monitoring systems dedicated to six major fields of application: waste management, homeland security, laboratories, health physics, continuous process monitoring and environmental monitoring.

Please visit [www.nuviatech-instruments.com](http://www.nuviatech-instruments.com) and [www.nuviatech-healthcare.com](http://www.nuviatech-healthcare.com) for more information.